

Electronic Ballasts

PARsource's standard electronic ballasts are more efficient compared to traditional magnetic ballasts. An internal electronic microprocessor allows the ballasts to run at a higher working frequency, creating a higher lumen output. This higher output means you can run fewer fixtures and save on energy and equipment costs, compared to traditional magnetic ballasts. PARsource ballasts come fully equipped with our patented Lock & Seal connector and a universal reflector adapter, all protected by our 2-year warranty. Ballasts power both metal halide and high pressure sodium lamps. Ask your PARsource representative for proper bulb pairings.



GLS Attached Electronic Ballast

Features

- More lumen output and more energy efficient than magnetic ballasts
- Run fewer fixtures for same light, resulting in equipment and energy savings
- Silent operation
- Smaller, lighter weight
 - 7 to 11 lbs; easier to install
 - Less shadow on greenhouse crop
- For use with metal halide or high pressure sodium lamps
 - Added flexibility for specific light wavelength selection
- Wall mount or hang
- Available in 400 and 600W
- Available voltages: 120, 208, and 240 volts (Lead time may vary for specific voltages)
- Patented Lock & Seal Plug System
- Sealed ballast for greenhouse environments
- Some combinations are CSA or UL listed
- 2-year warranty on ballast components

Includes

- Ballast with lamp cord
- 8' power cord and plug to match requested voltage
- Remote ballast system
- "C" brackets
- Hanging bar

Options

- Extension cord for remote applications (Item CSXCORD)



Applications



Indoor Growing



Medicinal



Propagation



Research



Supplemental Light

Crops



Annuals



Herbs



House Plants



Shrubs



Vegetables

PARsource Electronic Ballasts

Remote ballasts must be used with lock and seal extension cord.

ITEM	BALLAST LOCATION	DESCRIPTION	VOLTAGE	WATTS	AMPS	WT (LBS)	DIMENSIONS
GLE6120	Remote	600W/120V Electronic Ballast	120V	600	5.5	10.5	7.25" W x 10.5" L x 4.3" H
GLE6120A	Attached						
GLE6240	Remote	600W/240V Electronic Ballast	208V/240V	600	3.12/2.72	10.5	7.25" W x 10.5" L x 4.3" H
GLE6240A	Attached						
GLE4120	Remote	400W/120V Electronic Ballast	120V	400	3.6	7.75	4.5" W x 10.5" L x 4.5" H
GLE4120A	Attached						
GLE4240	Remote	400W/240V Electronic Ballast	208V/240V	400	2.07/1.80	7.75	4.5" W x 10.5" L x 4.5" H
GLE4240A	Attached						